

GROUT COLORANT

DESCRIPTION:

AQUA MIX GROUT COLORANT is an easy-to-use waterborne epoxy that re-colors, seals and rejuvenates existing grout joints. Also simplifies ongoing grout cleaning.

Aqua Mix Low VOC (Volatile Organic Compound Formulas) help provide better indoor and outdoor air quality compared to similar traditional products. 55 grams of VOC's per liter of material.

USES:

Sanded, un-sanded and epoxy grout joints. Effective for interior and exterior applications.

TEST A SMALL AREA:

According to application instructions, with a minimum 1-hour cure time to determine desired results.

EXPECTED WEAR UP TO 15 YEARS:

Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used. Weather conditions, harsh cleaning methods and high-alkaline, acidic or solvent-based cleaners will affect wear.

APPLICATION:

- 1) Read entire label before using.
- 2) SHAKE WELL before using.
- 3) For new installations, Grout Colorant can be applied as soon as 48 hours after grouting.
- 4) Grout joints must be clean, dry and free of existing sealers or coatings.
- 5) Prepare existing grout joints: MOST TILE & STONE: Use Aqua Mix Grout Colorant Pre-Treat Cleaner or Aqua Mix Phosphoric Acid Substitute. ACID-SENSITIVE STONE: Use Aqua Mix Heavy Duty Tile & Grout Cleaner EPOXY GROUT JOINTS: Use Aqua Mix Sealer & Coating Remover.
- 6) If more than 1 bottle of a single color is to be used, mix the material together in a large container to ensure uniformity of color.
- 7) If using Grout Colorant Applicator, pour Grout Colorant into Applicator bottle and apply a bead onto grout joint.
- 8) Spread evenly using the Applicator Brush or toothbrush, working Grout Colorant into joint using a back-and-forth motion. Thin, even coats should be applied, limiting the amount of Grout Colorant that gets on the tile.
- 9) If going from a dark to light grout color, more than 1 application may be necessary with a minimum 2-hour drying time between coats.
- 10) After Grout Colorant has dried 1 or more hours (never more than 12 hours), lightly mist surface with water and let stand 5 minutes. Remove excess Grout Colorant from surface of tile using water and a white nylon scrub pad.
- 11) Ready for surface traffic in 2 hours. Keep area dry for at least 24 hours. Avoid direct scrubbing on grout joints for 20 days to allow a full cure.
- 12) Clean applicator tools with water after each use.

LIMITATIONS:

- Grout Colorant is not recommended for use under water in pools, ponds, or on areas subject to hydrostatic pressure..
- Do not use solvent-based cleaners on re-colored grout joints.
- Previously applied sealers, with the exception of Aqua Mix Penetrating Sealer, Aqua Mix Grout Sealer, Aqua Mix Pro-Solv™, Aqua Mix Ultra-Solv™ or Aqua Mix Sealer's Choice Gold, must be removed to provide a bondable surface. Aqua Mix Sealer & Coating Remover is recommended for this procedure.
- Porous tile may require sealing to ensure colorant is not absorbed into the tile.

HANDLING AND STORAGE:

- Close container after each use.
- Store in original container only.
- Use in temperatures between 50°F and 80°F (10° C and 27° C).

CAUTION:

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains styrene-acrylic copolymer. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

KEEP OUT OF REACH OF CHILDREN

LIMITED PRODUCT WARRANTY Custom Building Products ("Custom") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

COVERAGE:
 Approximately 50 to 300 sq. ft. (5 m² to 28 m²) per 8-oz (237 ml) bottle depending on width and porosity of grout joint, size of tile, and method of application.

ORDERING INFORMATION:

Item Code US	Item Code Canada	Color	Size
063001	Co63001	White	8 oz. Bottle
063002	Co63002*	Antique White	8 oz. Bottle
063003	Co63003	Linen White	8 oz. Bottle
063004	Co63004*	Navajo	8 oz. Bottle
063005	Co63005*	Buff	8 oz. Bottle
063006	Co63006*	Sand	8 oz. Bottle
063007	Co63007*	Beige	8 oz. Bottle
063008	Co63008	Wheat	8 oz. Bottle
063009	Co63009*	Cinnamon	8 oz. Bottle
063010	Co63010	Cocoa	8 oz. Bottle
063011	Co63011	Light Gray	8 oz. Bottle
063014	Co63014	Black	8 oz. Bottle
063015	Co63015*	Bright White	8 oz. Bottle
063016	Co63016	Canvas	8 oz. Bottle
063017	Co63017*	Smoke	8 oz. Bottle
063021	Co63021*	Silver	8 oz. Bottle
063022	Co63022	Natural Gray	8 oz. Bottle
063023	Co63023*	Pewter	8 oz. Bottle
063024	Co63024	Charcoal Gray	8 oz. Bottle
063025	Co63025	Pure White	8 oz. Bottle

*Indicates a special order item.