

MATERIAL SAFETY DATA SHEET

EasyMat with SoundGard Technology (with Peel-n-Stick Adhesive)

HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

1. Product And Company Identification

Supplier CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3 Santa Fe Springs, CA 90670 UNITED STATES Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103 FAX Number: (562) 903-2697 E-Mail: georgem@cbpmail.net Web Site: www.custombuildingproducts.com	Manufacturer CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3 Santa Fe Springs, CA 90670 UNITED STATES Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103 FAX Number: (562) 903-2697 E-Mail: georgem@cbpmail.net Web Site: www.custombuildingproducts.com
Supplier Emergency Contacts & Phone Number GEORGE MARCINA: (562) 968-2980	Manufacturer Emergency Contacts & Phone Number GEORGE MARCINA: (562) 968-2980

Issue Date: 12/14/2006

Product Name: EasyMat with SoundGard Technology (with Peel-n-Stick Adhesive)

Chemical Name: Polypropylene Foam

CAS Number: Not Established

MSDS Number: 795

Product Code: SGL

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
Polyurethane Adhesive	Not Establish	1 - 10
Modified Asphalt	Not Establish	1 - 5
Polypropylene Foam	9010-79-1	90 - 99

3. Hazards Identification

Primary Routes(s) Of Entry

Inhalation, Skin Contact, Eye Contact, Ingestion

Eye Hazards

May cause eye irritation.

Skin Hazards

May cause mild irritation.

Ingestion Hazards

May cause gastronomical track irritation.

MATERIAL SAFETY DATA SHEET

EasyMat with SoundGard Technology (with Peel-n-Stick Adhesive)

3. Hazards Identification - Continued

Inhalation Hazards

May cause mild respiratory tract irritation.

Chronic/Carcinogenicity Effects

Contains modified asphalt which may contain traces of chemicals that are on CA Proposition 65 List

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Wash skin with soap and plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Ingestion

Get medical attention immediately.

Inhalation

If inhaled, remove to fresh air. Consult a physician immediately if irritation persists. Do not give an unconscious person anything to drink.

5. Fire Fighting Measures

Flash Point: N/A °F

Flash Point Method: N/A

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Fire And Explosion Hazards

Heat may melt and decompose the product generating flammable vapors.

Extinguishing Media

Dry Chemical, CO2, Foam,

Fire Fighting Instructions

Avoid breathing vapors, gases and fumes. Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Avoid generating dust. Sweep up and remove immediately. Use appropriate personal protective equipment.

7. Handling And Storage

Handling And Storage Precautions

Use with adequate ventilation.

Handling Precautions

Avoid creating and breathing dust. Avoid contact with skin and eyes.

Storage Precautions

Keep dry until ready to use. Store away from heat and sources of ignition.

Work/Hygienic Practices

Use good personal hygiene. Wash with soap and water after handling.

MATERIAL SAFETY DATA SHEET

EasyMat with SoundGard Technology (with Peel-n-Stick Adhesive)

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate ventilation.

Eye/Face Protection

Safety glasses to prevent dust injury.

Skin Protection

Not considered skin hazard. Wear gloves to prevent transfer of adhesive to skin.

Respiratory Protection

In case of inadequate ventilation and when exposed to dust above the recommended limits, wear a suitable NIOSH-approved respirator.

Ingredient(s) - Exposure Limits

Modified Asphalt

ACGIH TLV-TWA 0.5 mg/m³

Polypropylene Foam

OSHA TWA - 15 mg/m³ - Total dust

ACGIH TWA - 10 mg/m³ - Respirable fraction

9. Physical And Chemical Properties

Appearance

Light gray sheet with pressure sensitive adhesive.

Chemical Type: Mixture

Physical State: Solid

Specific Gravity: 0.1

Solubility: Negligible

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

Avoid heat.

Incompatible Materials

Hazardous Decomposition Products

Highly unlikely under normal use conditions.
Stable

11. Toxicological Information

Chronic/Carcinogenicity

Contains modified asphalt which may contain traces of chemicals that are on CA Proposition 65 List

Ingredient(s) - Carcinogenicity

Modified Asphalt

Listed In The IARC Monographs

MATERIAL SAFETY DATA SHEET

EasyMat with SoundGard Technology (with Peel-n-Stick Adhesive)

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

RCRA Information

Not considered RCRA Hazardous Waste.

14. Transport Information

DOT Shipping Label

NOT REGULATED

15. Regulatory Information

SARA Section 313 Notification

This product does not contain toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Ingredient(s) - State Regulations

Modified Asphalt

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

16. Other Information

HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

Personal Protection: B

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (562) 968-2980 ext 103

This MSDS Supersedes A Previous MSDS Dated: 11/07/2006

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000