

MATERIAL SAFETY DATA SHEET

TILE LAB GROUT HAZE REMOVER

HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	E

1. Product And Company Identification

Supplier

CUSTOM BUILDING PRODUCTS
10400 Pioneer Blvd., Unit #3
Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (562) 968-2980 Ext 103
FAX Number: (562) 903-2697
E-Mail: georgem@cbpmail.net
Web Site: www.custombuildingproducts.com

Manufacturer

CUSTOM BUILDING PRODUCTS
10400 Pioneer Blvd., Unit #3
Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (562) 968-2980 Ext 103
FAX Number: (562) 903-2697
E-Mail: georgem@cbpmail.net
Web Site: www.custombuildingproducts.com

Supplier Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Manufacturer Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Issue Date: 03/22/2006

Product Name: TILE LAB GROUT HAZE REMOVER
CAS Number: Not Established
Chemical Formula: Mixture
MSDS Number: 582
Product Code: 3062

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
GLYCOLIC ACID	79-14-1	5 - 15

3. Hazards Identification

Primary Routes(s) Of Entry

Inhalation
Skin Contact
Eye Contact
Ingestion

Eye Hazards

Can cause eye corrosion with corneal or conjunctival ulceration. Can cause permanent eye injury.

Skin Hazards

Can cause severe skin irritation. Prolonged exposure can cause skin burns or ulceration.

Ingestion Hazards

Ingestion maybe harmful. Seek medical attention. Swallowing may cause corrosion of mucous membranes and stomach discomfort, nausea and prostration. Gross overexposure can cause kidney damage or even a fatality.

MATERIAL SAFETY DATA SHEET

TILE LAB GROUT HAZE REMOVER

3. Hazards Identification - Continued

Inhalation Hazards

Inhalation maybe cause irritation of mucous membranes and irritation of upper respiratory and bronchial tracts.

Subchronic (Target Organ Effects)

Chronic/Carcinogenicity Effects

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Remove individual to fresh air. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with plenty of water and wash with soap for at least 15 minutes. Remove contaminated clothing. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

Get medical attention immediately. If the victim is unconscious or drowsy do not give anything by mouth. If the individual is conscious and alert, immediately rinse mouth with water and give 2 glasses of water to drink.

Inhalation

If inhaled, remove to fresh air. Consult a physician immediately. Do not give an unconscious person anything to drink. If necessary give artificial respiration. If breathing is difficult, give oxygen.

5. Fire Fighting Measures

Flash Point: N/A °F

Flash Point Method: N/A

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Fire And Explosion Hazards

Material will not burn until dry.

Extinguishing Media

Foam, dry chemical, carbon dioxide, water.

Fire Fighting Instructions

Wear self contained breathing apparatus and protective suit.

6. Accidental Release Measures

Contain spill with inert material such as sand or earth. Transfer to suitable containers for disposal.

7. Handling And Storage

Handling And Storage Precautions

Use only with adequate ventilation.

Handling Precautions

Avoid contact with skin and clothing. Avoid contact with eyes. Wash contaminated clothing before re-use.

MATERIAL SAFETY DATA SHEET

TILE LAB GROUT HAZE REMOVER

7. Handling And Storage - Continued

Storage Precautions

Keep in cool and dry area.

Work/Hygienic Practices

Use good personal hygiene. Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate ventilation.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

If hands or feet will be exposed, wear impervious gloves and/or boots.

Respiratory Protection

In case of inadequate ventilation and when exposed to dust above the recommended limits, wear a suitable NIOSH-approved respirator.

9. Physical And Chemical Properties

Appearance

Clear liquid

Odor

May have very slight odor.

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 210 °F 100 °C

Specific Gravity: 1.1

Percent Volatiles: 95

Percent VOCs: 74g/l

Vapor Pressure: Same as water

Vapor Density: N/A

pH Factor: 1 - 2

Solubility: Dilutable

Viscosity: Water like

Evaporation Rate: N/A

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

Avoid heat.

Incompatible Materials

Strong oxidizing agents.

11. Toxicological Information

No Data Available...

MATERIAL SAFETY DATA SHEET

TILE LAB GROUT HAZE REMOVER

12. Ecological Information
No Data Available...
13. Disposal Considerations
Dispose in accordance with applicable federal, state and local government regulations. RCRA Information Not considered RCRA Hazardous Waste.
14. Transport Information
DOT Shipping Label NOT REGULATED
15. Regulatory Information
SARA Section 313 Notification
16. Other Information
HMIS Rating Health: 1 Fire: 0 Reactivity: 0 Personal Protection: E Revision/Preparer Information MSDS Preparer: GEORGE MARCINA MSDS Preparer Phone Number: (323) 582-0846 This MSDS Supersedes A Previous MSDS Dated: 03/20/2006
Disclaimer
Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s). CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000